



- ◆ EcoTouch® insulation
- ◆ Certified to include 58% total recycled content, including a minimum of 36% post-consumer recycled content
- ◆ GREENGUARD Children & Schools certified and verified to be formaldehyde free
- ◆ Contains more than 99% natural ingredients
- ◆ Enable home and building to achieve energy-efficiency and green building certifications



- ◆ Cellulose provides a higher R value per inch than fiberglass
- ◆ Cellulose “tightens” buildings better, fitting easily around pipes and electrical wiring
- ◆ Class 1, Type A building material
- ◆ Highest recycled content - Cellulose insulation is 85% recycled paper fiber
- ◆ Chemically blended product with stabilizer

## Insulation



Johns Manville Kraft Faced Fiberglass Insulation

- ◆ ASTM Standards, ASTM C665, Type II, Class C, Category 1
- ◆ Water Vapor Permeance Facing, ASTM E96, 1.0 perms
- ◆ Water Vapor Sorption, WSTM C1104, 5% or less by weight
- ◆ Odor Emission, ASTM C1304
- ◆ Corrosiveness, ASTM 665
- ◆ Fungi Resistance, ASTM C1388



R-Matte® Plus-3 is a rigid foam plastic thermal insulation board composed of environmentally sound, closed cell, polyisocyanurate foam bonded to a durable white-matte (non-glare) aluminum facer and a reflective reinforced aluminum facer.

- ◆ 3/4” Foam Polyboard, provides R value us 5.0
- ◆ Impermeable foil facing the repels water and guards against air infiltration
- ◆ Complies with: ASTM C1289 Type I, Class 1, Air barrier material per ASTM E2178
- ◆ R-Matte Plus-3 is Energy Star approved